| Product Safety Ir | nformation Sheet |
|-------------------|------------------|
|-------------------|------------------|

< OUPONT .

DELRIN ® acetal resin

Ref. 150000000569 Version 2.5 (replaces: Version 2.4)

Revision Date 11.02.2021 Issue Date 11.02.2021

This Product Safety Information Sheet is provided as general information for health and safety guidance.

| SECTION 1: Identification of the | substance/mixture and of the company/undertaking |
|----------------------------------|--|
| Product identifier | |
| Product name | : DELRIN ® acetal resin |
| Types | 23P, 45P, 100P, 111DP, 111P, 111PA, 150, 500CP, 500P, 511DP, 511P, 588P, 900P, 911DP, 911P, 1700P, 1700SL, 127UV, 327UVE, 527UV, 927UV, 1727UV, 142CM, 300CP, 311DP, 390PM, 500LM, 542CM, 988PA, DE20130, DE20199, DE20321, DE20427, DE20308, HG900P, M509, M590 (1); 300AT (2) RA347UVE, RA500P |
| Recycling code | : 1) ISO 11469 : >POM<; 2) ISO 11469 : >POM-ICD< |
| Relevant identified uses of th | e substance or mixture and uses advised against |
| Use of the Substance/Mixture | : Resin for moulding and/or extrusion |
| Details of the supplier | |
| Company | : Performance Specialty Products Iberica S.L. Avda. Diagonal, 571 ES-08029 Barcelona Spain |
| Telephone | : +34-98-512-4000 |
| Telefax | : +34-98-512-4090 |
| E-mail address | : sds-support@dupont.com |
| Emergency telephone numbe | r |
| Emergency telephone number | : +(44)-870-8200418 (CHEMTREC) |
| SECTION 2: Hazards identificatio | n |
| Classification of the substant | ce or mixture |
| Classification according to R | egulation (EU) 1272/2008 (CLP) |
| Not a classified substance or m | ixture according to Regulation (EC) No. 1272/2008. |
| Label elements | |
| Labelling according to Regu | lation (EU) 1272/2008 (CLP) |
| | |
| | |

| | OUPONT CONTRACTOR CONTRACTOR Sheet |
|--|---|
| DELRIN ® acetal resi | า |
| Ref. 150000000569 /ersion 2.5 (replaces: Version 2 | Revision Date 11.02.2021 (.4) Issue Date 11.02.2021 |
| Not a classified substance | or mixture according to Regulation (EC) No. 1272/2008. |
| Other hazards | |
| (PBT), or very persistent and Hazardous decomposition p Formaldehyde | ains no components considered to be either persistent, bioaccumulative and toxic d very bioaccumulative (vPvB) at levels of 0.1% or higher. roducts yde as a substance with possible risk of irreversible effect. |
| ECTION 3: Composition/info | rmation on ingredients |
| Chemical nature of the | : Polyoxymethylene homopolymer |
| substance/mixture | : Additives |
| | |
| ECTION 4: First aid measure Description of first aid me | |
| | |
| Description of first aid me | Remove from exposure, lie down. Never give anything by mouth to an unconscious person. No hazards which require special first aid measures. If a |
| Description of first aid me General advice | Remove from exposure, lie down. Never give anything by mouth to an unconscious person. No hazards which require special first aid measures. If a person vomits when lying on his back, place him in the recovery position. Move to fresh air in case of accidental inhalation of fumes from overheating or |
| Description of first aid me General advice Inhalation | Remove from exposure, lie down. Never give anything by mouth to an unconscious person. No hazards which require special first aid measures. If a person vomits when lying on his back, place him in the recovery position. Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Consult a physician after significant exposure. Cool skin rapidly with cold water after contact with molten material. Do not peer |
| Description of first aid me General advice Inhalation Skin contact | Remove from exposure, lie down. Never give anything by mouth to an unconscious person. No hazards which require special first aid measures. If a person vomits when lying on his back, place him in the recovery position. Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Consult a physician after significant exposure. Cool skin rapidly with cold water after contact with molten material. Do not peep polymer from the skin. Obtain medical attention. |
| Description of first aid me General advice Inhalation Skin contact Eye contact Ingestion | Remove from exposure, lie down. Never give anything by mouth to an unconscious person. No hazards which require special first aid measures. If a person vomits when lying on his back, place him in the recovery position. Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Consult a physician after significant exposure. Cool skin rapidly with cold water after contact with molten material. Do not pee polymer from the skin. Obtain medical attention. Flush eyes with water as a precaution. Obtain medical attention. No hazards which require special first aid measures. Drink water as a precaution. |
| Description of first aid ma General advice Inhalation Skin contact Eye contact Ingestion ECTION 5: Firefighting meas | Remove from exposure, lie down. Never give anything by mouth to an unconscious person. No hazards which require special first aid measures. If a person vomits when lying on his back, place him in the recovery position. Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Consult a physician after significant exposure. Cool skin rapidly with cold water after contact with molten material. Do not pee polymer from the skin. Obtain medical attention. Flush eyes with water as a precaution. Obtain medical attention. No hazards which require special first aid measures. Drink water as a precaution. |
| Description of first aid me General advice Inhalation Skin contact Eye contact Ingestion | Remove from exposure, lie down. Never give anything by mouth to an unconscious person. No hazards which require special first aid measures. If a person vomits when lying on his back, place him in the recovery position. Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Consult a physician after significant exposure. Cool skin rapidly with cold water after contact with molten material. Do not pee polymer from the skin. Obtain medical attention. Flush eyes with water as a precaution. Obtain medical attention. No hazards which require special first aid measures. Drink water as a precaution. |

OUPONT

DELRIN ® acetal resin

against fire and explosion

| Ref. 150000000569 Version 2.5 (replaces: Version 2.4) | Revision Date 11.02.2021 Issue Date 11.02.2021 |
|--|--|
| Suitable extinguishing media | : Carbon dioxide (CO2), Dry powder, Foam, Water |
| Special hazards arising from | the substance or mixture |
| Specific hazards during firefighting | : Large molten masses may ignite spontaneously in air. Water quenching is good practice. Under conditions giving incomplete combustion, hazardous gases produced may consist of: Carbon monoxide Carbon dioxide (CO2) (see also section 10) |
| Advice for firefighters | |
| Special protective equipment for firefighters | : In the event of fire, wear self-contained breathing apparatus. Wear suitable protective equipment. |
| Further information | : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Do not allow run-off from fire fighting to enter drains or water courses. Burns after ignition without external heat source (IEC 60695-11-10 : HB). Burns with colourless flame. |
| SECTION 6: Accidental release m | easures |
| Personal precautions, protect | ctive equipment and emergency procedures |
| Personal precautions | : Ventilate the area. Refer to protective measures listed in sections 7 and 8. |
| Environmental precautions | |
| Environmental precautions | : Try to prevent the material from entering drains or water courses. Do not contaminate surface water. |
| Methods and materials for co | ontainment and cleaning up |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Sweep up or vacuum up spillage and collect in suitable container for disposal. |
| Other information | : Use mechanical handling equipment. |
| | |
| SECTION 7: Handling and storage | |
| Precautions for safe handling | 9 |

| Advice on safe handling | : | Protect from contamination. When opening containers, avoid breathing vapours that may be emanating. Open container only in well-ventilated area. Provide appropriate exhaust ventilation at dryers, machinery and at places where dust or volatiles can be generated. General precaution for all plastics and elastomers: For personal protection see section 8. In case of insufficient ventilation, wear suitable respiratory equipment. No special handling advice required. |
|-------------------------|---|---|
| Advice on protection | : | Take necessary action to avoid static electricity discharge (which might cause |

ignition of organic vapours).

< OUPONT .

DELRIN ® acetal resin

| Ref. 15000000569 |
|-------------------------------------|
| Version 2.5 (replaces: Version 2.4) |
| |

Revision Date 11.02.2021 Issue Date 11.02.2021

| Dust explosion class | : | no data available | |
|---|------|---|--|
| Conditions for safe storage | , ir | cluding any incompatibilities | |
| Requirements for storage areas and containers | : | No special storage conditions required. Keep container tightly closed in a dry and well-ventilated place. Protect from contamination. | |
| Further information on storage conditions | : | none | |
| Advice on common storage | : | No special restrictions on storage with other products. | |
| Other data | : | No decomposition if stored and applied as directed. | |
| | | | |

SECTION 8: Exposure controls/personal protection

If sub-section is empty then no values are applicable. For further information on any control parameters provided, please refer to the relevant regulation.

| Exposure controls | | |
|--------------------------|---|---|
| Engineering measures | : | When hot processing this material, use local and/or general exhaust ventilation to maintain the concentration of vapors and fumes below exposure limits. |
| Eye protection | : | Safety glasses with side-shields Wear tightly fitting chemical splash goggles and face shield when possibility exists for eye and face contact due to spattering or splashing of molten material. |
| Hand protection | : | Material: Heat insulating gloves Protective gloves (Type : Kevlar [®] - heat resistant, use possible until worn out) |
| Skin and body protection | ÷ | If there is a potential for contact with hot/molten material wear heat resistant clothing and footwear. Regular cleaning of equipment, work area and clothing. |
| Hygiene measures | : | Wash hands before breaks and at the end of workday. General precaution for all plastics and elastomers: Do not breathe fumes evolved from hot polymer. |
| Respiratory protection | : | When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Suitable respiratory equipment: Half mask with a particle filter FFP2/FFP3 (EN149) |

| SECTION 9: Physical and chemical properties | | |
|---|----------------------------------|--|
| Information on basic | physical and chemical properties | |
| Form | : pellets | |
| Colour | : various | |
| | 4/8 | |

OUPONT

DELRIN ® acetal resin

| f. 150000000569 rsion 2.5 (replaces: Version 2.4) | Revision Date 11.02.2021) Issue Date 11.02.2021 |
|--|--|
| Odour | : formaldehyde-like |
| рН | : Not applicable |
| Melting point/range | : 172 - 184 °C |
| Flash point | : Not applicable |
| Ignition temperature | : 375 °C |
| Thermal decomposition | : > 230 °C |
| Density | : 1,35 - 1,45 g/cm3 , Method: ISO 1183 |
| Water solubility | : insoluble |
| Other information | |
| No other data to be specially m | nentioned. |
| CTION 10: Stability and reacti Possibility of hazardous reactions | None. Further information : During drying, cleaning and moulding, small amounts of hazardous gases and/or particulate matter may be released. Thes may irritate eyes, nose and throat. Large molten masses may give off |
| Possibility of hazardous | None. Further information : During drying, cleaning and moulding, small amounts of hazardous gases and/or particulate matter may be released. These |
| | None. Further information : During drying, cleaning and moulding, small amounts of hazardous gases and/or particulate matter may be released. These may irritate eyes, nose and throat. Large molten masses may give off hazardous gases. Water quenching is good practice. Stable under normal |
| Possibility of hazardous reactions | None. Further information : During drying, cleaning and moulding, small amounts of hazardous gases and/or particulate matter may be released. These may irritate eyes, nose and throat. Large molten masses may give off hazardous gases. Water quenching is good practice. Stable under normal conditions. Avoid heating for prolonged periods above the recommended upper processin |
| Possibility of hazardous reactions | None. Further information : During drying, cleaning and moulding, small amounts of hazardous gases and/or particulate matter may be released. These may irritate eyes, nose and throat. Large molten masses may give off hazardous gases. Water quenching is good practice. Stable under normal conditions. Avoid heating for prolonged periods above the recommended upper processin limit. Strong acids and oxidizing agents Strong bases halogenated compounds, except those already present in the formulation as |
| Possibility of hazardous reactions Conditions to avoid Incompatible materials Hazardous decomposition products | None. Further information : During drying, cleaning and moulding, small amounts of hazardous gases and/or particulate matter may be released. These may irritate eyes, nose and throat. Large molten masses may give off hazardous gases. Water quenching is good practice. Stable under normal conditions. Avoid heating for prolonged periods above the recommended upper processin limit. Strong acids and oxidizing agents Strong bases halogenated compounds, except those already present in the formulation as supplied Formaldehyde |
| Possibility of hazardous reactions Conditions to avoid Incompatible materials Hazardous decomposition products CTION 11: Toxicological infor | None. Further information : During drying, cleaning and moulding, small amounts of hazardous gases and/or particulate matter may be released. These may irritate eyes, nose and throat. Large molten masses may give off hazardous gases. Water quenching is good practice. Stable under normal conditions. Avoid heating for prolonged periods above the recommended upper processin limit. Strong acids and oxidizing agents Strong bases halogenated compounds, except those already present in the formulation as supplied Formaldehyde |
| Possibility of hazardous reactions Conditions to avoid Incompatible materials Hazardous decomposition products CTION 11: Toxicological infor The product contains no subs | None. Further information : During drying, cleaning and moulding, small amounts of hazardous gases and/or particulate matter may be released. These may irritate eyes, nose and throat. Large molten masses may give off hazardous gases. Water quenching is good practice. Stable under normal conditions. Avoid heating for prolonged periods above the recommended upper processin limit. Strong acids and oxidizing agents Strong bases halogenated compounds, except those already present in the formulation as supplied Formaldehyde |

< DUPONT .

DELRIN ® acetal resin

Ref. 150000000569 Version 2.5 (replaces: Version 2.4) Revision Date 11.02.2021 Issue Date 11.02.2021

SECTION 13: Disposal considerations

Waste treatment methodsProduct: Like most thermoplastic plastics the product can be recycled. Where possible
recycling is preferred to disposal or incineration. If recycling is not practicable,
dispose of in compliance with local regulations. Can be landfilled, when in
compliance with local regulations. Do not contaminate ponds, waterways or
ditches with chemical or used container.Contaminated packaging: Empty containers should be taken to an approved waste handling site for
recycling or disposal.European Waste Catalogue
number: 07 02 99: Wastes not otherwise specified.

SECTION 14: Transport information

ADR

| | | 6/8 |
|-------|---|--|
| Safet | y, nealth and environmental reg | ulations/legislation specific for the substance or mixture |
| | 15: Regulatory information | |
| | •• | |
| 14.7. | Transport in bulk according to An Not applicable | nex II of Marpol and the IBC Code |
| | C C | |
| 14.0. | | e meaning of transport regulations. |
| 146 | Special precautions for user: | |
| 14.5. | Environmental hazards: | none |
| | Packing group: | Not applicable |
| 14.3. | Transport hazard class(es): | Not applicable |
| | UN proper shipping name: | Not applicable |
| | UN number: | Not applicable |
| IMDG | | |
| | Not classified as dangerous in the | e meaning of transport regulations. |
| 14.6. | Special precautions for user: | |
| 14.5. | | none |
| | Packing group: Environmental hazards: | Not applicable none |
| | Transport hazard class(es): | Not applicable |
| | UN proper shipping name: | Not applicable |
| | UN number: | Not applicable |
| | | |
| | Not oldosined as dangerous in the | s meaning of transport regulations. |
| 14.6. | Special precautions for user: Not classified as dangerous in the | e meaning of transport regulations. |
| | | |
| | Packing group: Environmental hazards: | none |
| | Transport hazard class(es): | Not applicable Not applicable |
| | UN proper shipping name: | Not applicable |
| | | |

OUPONT

DELRIN ® acetal resin

Ref. 15000000569 Version 2.5 (replaces: Version 2.4)

Revision Date 11.02.2021 Issue Date 11.02.2021

Other regulations :

No specific information about other regulations/legislation to be mentioned.

SECTION 16: Other information

Abbreviations and acronyms

| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
|---------|---|
| ATE | Acute toxicity estimate |
| CAS-No. | Chemical Abstracts Service number |
| CLP | Classification, Labelling and Packaging |
| EbC50 | Concentration at which 50% reduction of biomass is observed |
| EC50 | Median effective concentration |
| EN | European Norm |
| EPA | Environmental Protection Agency |
| ErC50 | Concentration at which a 50% inhibition of growth rate is observed |
| EyC50 | Concentration at which 50 % inhibition of yield is observed |
| IATA_C | International Air Transport Association (Cargo) |
| IBC | International Bulk Chemical Code |
| ICAO | International Civil Aviation Organization |
| ISO | International Standard Organization |
| IMDG | International Maritime Dangerous Goods |
| LC50 | Median Lethal Concentration |
| LD50 | Median Lethal Dose |
| LOEC | Lowest Observed Effect Concentration |
| LOEL | Lowest observed effect level |
| MARPOL | International Convention for the Prevention of Marine Pollution from Ships |
| n.o.s. | Not Otherwise Specified |
| NOAEC | No Observed Adverse Effect Concentration |
| NOAEL | No observed adverse effect level |
| NOEC | No Observed Effect Concentration |
| NOEL | No Observed Effect Level |
| OECD | Organisation for Economic Co-operation and Development |
| OPPTS | Office of Prevention, Pesticides and Toxic Substances |
| PBT | Persistent, Bioaccumulative and Toxic |
| STEL | Short term exposure limit |
| TWA | Time Weighted Average (TWA): |
| vPvB | very Persistent and very Bioaccumulative |

Restrictions on use

Do not use DuPont materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless the material has been provided from DuPont under a written contract that is consistent with DuPont policy regarding medical applications and expressly acknowledges the contemplated use. For further information, please contact your DuPont representative. You may also request a copy of the DuPont POLICY Regarding Medical Applications and DuPont CAUTION Regarding Medical Applications.

Further information

< DUPONT >

DELRIN ® acetal resin

Ref. 15000000569 Version 2.5 (replaces: Version 2.4)

Revision Date 11.02.2021 Issue Date 11.02.2021

Before use read DuPont's safety information.

[®] Registered trademark of E.I. du Pont de Nemours and Company

[™] Trademark of E.I. du Pont de Nemours and Company.

An Exposure Scenario (ES) is not required.

Significant change from previous version is denoted with a double bar.

The information provided in this Product Safety Information Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific materials(s) designated herein and may not be valid for such materials or in any process or if the material is altered or processed, unless specified in the text.